

# DAVEY ProMatic Lifeguard



WIFI  
ENABLED



RESIDENTIAL



SALT WATER  
SANITISER

RELAX. LIFEGUARD  
DOES ALL THE  
THINKING FOR YOU.

## APPLICATION

Ideal for in-ground and above ground residential swimming pools. Designed for salt and mineral salt pools. Models suitable for pools up to 175m<sup>3</sup>.

## ALL NEW COMPLETE POOL CHLORINATION & CHEMISTRY CONTROL SYSTEM

- WiFi enabled with fully integrated app (remote control can be deactivated)
- pH sensor and acid dosing, ORP control, temperature and salt measurement for effortless pool balancing
- ORP control to prevent over chlorination when pool cover is used
- Next generation high performance reverse polarity in-line cell with integrated safety flow switch
- Low salt cut off to protect the cell
- Boost Mode for additional chlorination during periods of heavy bather loads
- Comprehensive multilingual user-friendly LCD interface
- Operating Salt Level: 3000 – 6000ppm, 1500-6000ppm for low salt models

# DAVEY ProMatic Lifeguard

## Complete Pool Chlorination & Chemistry Control System



- New design high performance reverse polarity in-line cell with barrel unions for low maintenance and installation flexibility
- Integrated flow switch for better safety accommodating flows down to 3.6m<sup>3</sup>/hr for integration with variable speed pool pumps
- Included acid pump for maintaining pH
- LCD screens for user-friendly operation
- UV stabilised enclosures for strength and durability
- Easy to install, in line probe manifold with included probes and winter blanking plugs
- Fully integrated app for information and control

\*NOTE: Phone not included in package

DIMENSIONS All models (mm)	EcoSalt2				Lifeguard				Cell Housing				
	Height	Width	Depth	Mounting Holes	Height	Width	Depth	Mounting Holes	Height	Width	Diameter	Inlet	Outlet
	320	238	113	164	153	240	97	205	341	198	120	50	50

CHLORINE OUTPUT	Model	Chlorine Gas Production (g/hr 100%)	Calcium Hypochlorite (g/hr 65% equivalent)	Maximum Pool Size (m <sup>3</sup> )		
				Cool Climates <25°C	Temperate Climates 25°C to 30°C	Hot & Tropical Climates >30°C
	DPLG-15E	15	23	75	58	46
	DPLG-25E	25	38	125	96	80
	DPLG-35E	35	53	175	134	112
	DPLG-15EL	15	23	75	58	46
	DPLG-25EL	25	38	125	96	80

ELECTRICAL DATA All models	Voltage (V)	220-240
	Phase	1
	Supply Frequency (Hz)	50/60
	Enclosure Class (IP)	34
	Maximum Power (kW)	15g/hr: 0.12 25g/hr: 0.24 35g/hr: 0.24

### IMPORTANT NOTES

1. In 'hard water' applications (above 275ppm), reverse polarity systems will require regular (monthly) inspection and manual cleaning.
2. The appropriate sanitiser size for your pool is dependant on the local climate and the bather load of the pool. Please note that cell life can be increased with shorter running times during winter. Davey recommends that a sanitiser is run for between 6 – 8 hours a day during summer, and between 2 – 4 hours during winter.

CE RoHS

daveywater.com

This literature is not a complete guide to product usage. Further information is available from your Davey Dealer, Davey Support Centre and from the relevant product Installation and Operating Instructions. Must be read in conjunction with the relevant product Installation and Operating Instructions and all applicable statutory requirements. Product specifications may change without notice. © Davey is a registered trademark of Davey Water Products Pty Ltd. © Davey Water Products Pty Ltd 2022.

# DAVEY